

Advice sheet for determining cleaning procedure

Information document for determining a balanced cleaning procedure for Pulastic sports floors

- General information**
- ✓ A high-quality sports floor deserves high-quality maintenance, which is why Sika Nederland is providing an advice sheet for determining a balanced cleaning procedure.
 - ✓ The effect of using and the load exerted on the Pulastic sports floor is essential for choosing a cleaning regime.
 - ✓ This advice sheet is intended as an information document.
 - ✓ The use of resin (ball games) and/or magnesium (gymnastics) has direct consequences for choosing a cleaning regime in the room in question. Please contact the Pulastic team for advice.
 - ✓ For questions in the event of an alternative load or use of the Pulastic sports floor, please send an e-mail to: export@nl.sika.com or telephone: +31 570 620744.

Load factor	Low	Normal	High
Cleaning procedure	Amended procedure Sports facilities with a low load factor, during the day and for 2-3 days per week	Standard Pulastic advice Sports facilities with an average load, during the day and possibly in the evening and for 4-5 days per week	Amended procedure Sports facilities with a high load factor, during the day and in the evening and for 6-7 days per week
Removing marks	Weekly	Daily	Daily
Clearing dust	Three times a week	Daily	Twice a day
Wet cleaning with Pulastic Eco Clean or Pulastic Basic Clean	Once every two weeks using the 'indirect' method	At least once a week using the 'direct' method	At least three times a week using the 'direct' method Or, at least twice a week using the 'indirect' method
Periodic cleaning with Pulastic Deep Clean	Once to twice a year	Twice a year	Three times a year

Cleaning methods explained	'Direct' method	'Indirect' method
	<p>Step 1: Fill the scrubber's water tank with the cleaning product solution, making sure that the ratio is correct.</p> <p>Step 2: Place the red pad (scourer) under the scrubber.</p> <p>Step 3: The solution should then be scrubbed onto the floor and drained away again immediately.</p>	<p>Step 1: Fill the scrubber's water tank with the maintenance product solution, making sure that the ratio is correct.</p> <p>Step 2: Place the red pad (scourer) under the scrubber.</p> <p>Step 3: The solution should then be scrubbed onto the floor.</p> <p>Step 4: Allow the applied solution to absorb according to the directions on the maintenance product.</p> <p>PLEASE NOTE: Applied maintenance products must not be left behind or allowed to dry on the floor.</p> <p>Step 5: Then scrub away the applied solution using the scrubber.</p>
Statutory information	<p>The information, especially the recommendations that apply to the use and end use of Pulastic products, is provided in good faith based on current knowledge and experience of Pulastic products that have been stored and handled correctly and used under normal conditions. In practice, the differences in materials, underlays and actual on-site conditions are such that no guarantee can be derived in relation to marketability or suitability for a specific purpose, nor any liability resulting from any legal relationship based on this information, or from any written recommendations or any other advice that is given. Third-party property rights must be respected. All orders are accepted under current terms and conditions of sale and delivery. Users must consult the most recent edition of the technical information sheet for the product in question at all times, copies of which will be provided upon request.</p>	
